



Podet Km 23+045			
Nr. Crt.	X	Y	Z
P1	213833.837	479662.609	88.46
P2	213836.848	479654.499	88.43
P3	213840.032	479645.922	88.40

- Clasa de rezistentă la compresiune	C30/37
- Clasele de expunere (min)	XC4+XD1+XF4
- Dozaj minim de ciment (min)	340 kg/mc
- Tip ciment conf. SR EN 197-1:2011	CEM I; SRI; I-A 52.5, 42.5; CEM II: A/B-S, IIIA-S, A-LL;
- Raport apa/ciment (max)	0.5

- Clasa de rezistentă la compresie	C25/30
- Clasele de expunere (min)	XF2
- Dozaj minim de ciment (min)	300 kg/mc
- Tip ciment conf. SR EN 197-1:2011	CEM I; SRI; I-A 52.5, 42.5; CEM II: A/B-S, IIIA-S, A-LL
- Raport apa/ciment (max)	0.55a

- Clasa de rezistentă la compresie	C25/30
- Clasele de expunere (min)	XF1
- Dozaj minim de ciment (min)	300 kg/mc
- Tip ciment conf. SR EN 197-1:2011	CEM I; SRI; I-A 52.5, 42.5; CEM II: A/B-S, HIIA-S, A-LL;
- Raport apa/ciment (max)	0.5

- Clasa de rezistenta la compresiune	C16/20
- Clasele de expunere (min)	XC2
- Dozaj minim de ciment (min)	260 kg/mc
- Tip ciment conf. SR EN 197-1:2011	CEM I; SRI; I-A 52.5, 42.5; CEM II II: A/B-S, IIIA-S, A-LL;
- Raport apa/ciment (max)	0.60

